



Professional Pillar Drills



Model:	13A	16AE	16AT	16AEF	16ATF	25A
SKU:	761000	100762000	100763000	100764000	100765000	100766000
RPM [rpm]:	1400	180-2740	180-2740	280 to 2380	280-2380	120-3480
Voltage [V]:	1-Ph, 230V, 50 Hz	1-Ph, 230V, 50 Hz	3 x 400V - 50 Hz	1-Ph, 230V, 50 Hz	3-Ph, 400V, 50 Hz	3-Ph, 400V, 50 Hz
Motor [HP]:	1	1	1	1	1	1
Motor [kW]:	0.4	0,75	0,75	0,75	0,75	1,1
Drilling Capacity [ø mm]:	13	20	19	20	20	32
Taper:	n/a	MT2	MT2	MT2	MT2	MT4
Drill chuck [mm]:	13 / B16	16	16	16	16	16/B16
Throat depth [mm]:	n/a	190	190	190	190	254
Swing Capacity [mm]:	420	420	420	410	410	550
Spindel to Table [mm]:	n/a		465/685	720/1210	720/1210	710/1180
Throat Depth [mm]:	130	465 x 685	n/a	n/a	n/a	n/a
Table size [mm]:	162 x 162	285 x 285	285 x 285	285 x 285	285 x 285	475 x 425
Base Size [mm]:	290 x 186	480 x 270	480 x 270	480 x 270	480 x 270	575 x 445
Table Tilt Max. (+/-) [deg]:	n/a	45°	45°	45°	45°	45°
Spindle Travel Max. [mm]:	50	s	80	80	80	120
Spindle Speeds [qty]:	5	12	12	12	12	12
Reversible [y/n]:	No	No	Yes	No	Yes	Yes
Floor / Bench model:	Bench	Bench	Bench	Floor	Floor	Floor
Height [mm]:	730	1065	1065	1600	1600	1700
Net Weight [kg]:	25	61	61	67	67	125